

# MAUS Stixx Pro 5

## Art no 1360-1



MAUS Stixx PRO 5 is a fire suppression unit that automatically extinguishes fires in larger spaces in the event of a fire. With a capacity to protect spaces up to 0.5 m<sup>3</sup>, the MAUS Stixx PRO 5 is five times more powerful than MAUS Stixx PRO (which can only handle 0.1 m<sup>3</sup>). The small size but with its large capacity makes the product a unique fire protection product on the market. The product can also be equipped with a detector cable that can be attached to the unit, which means that you have greater and faster detection in larger power stations and switchgears.

The heat detecting cables are placed on the top of the unit and activates by exposure to fire or when the unit reaches 170°C. The extinguishing agent is sent out through the ports of the unit and quickly fills the enclosure and extinguishes the fire. You can also add an additional heat detecting cable that can be inserted on the side of the unit for larger heat detection for larger enclosures. The extinguishing agent consists of a non-toxic, environmentally friendly, patented potassium mixture that absorbs the heat and interrupts the chemical composition of the fire. A true innovation in firefighting.

### Advantages:

- Non-pressurized product.
- 100% activation on detection
- Activates at low temperature.
- Small size.
- Requires no maintenance.
- The extinguishing agent does not damage anything\*.

\*Potassium radicals are very active and they interrupt the chemical combustion reactions by neutralizing hydrogen, oxygen and hydroxide radicals in the flame.

### SPECIFICATIONS:

MAUS Pro Stixx 5	Automatic Fire Suppression Unit
Article no:	1360-1
EAN/Barcode:	7350015530225
Dimensions:	6 x 6 x 2 cm
Weight:	130 g
Warranty	5 years (6 years shelf life)
Exhaust time:	≤5s
Protected space:	0,5 m <sup>3</sup> (H100 x B100 x D50 cm)
Activation Temperature:	170°C±10°C
Operating Temperature:	-30°C - 70°C
Certifications:	CE 2829
Units per box:	1

CE 2829



MAUS Stixx PRO 5

*An additional heat detecting cable can be inserted on the side of the unit.*



MAUS Stixx PRO 5 product box.

### Important!

The MAUS Stixx Pro 5 needs 3 cm of space at the ports to be able to send out the extinguishing agent correctly. The unit is designed for closed enclosures. Ventilated spaces are not ideal for this technique.

### Where to install MAUS Stixx PRO 5:

- Electrical enclosures (standard cabinets, appliance cabinets, etc.)
- Switchgears
- Server rooms
- Engine compartments
- Motorhomes / RV's

MAUS™ is a registered trademark owned by Falkenheim Invest AB. Since 2015 MAUS have equipped the Swedish Police, the government owned postal service PostNord, Sandvik, Anticimex, corporate cars from Audi, VW, Volvo and Skoda with their products and innovative technology. Falkenheim Invest AB headquarter is based in Lidköping, Sweden.