

time counter, mechanical, 230V, 50Hz



Figure similar

| Model                                                   |                         |
|---------------------------------------------------------|-------------------------|
| product brand name                                      | SENTRON                 |
| product designation                                     | Mechanical time counter |
| type of the driving mechanism                           | others                  |
| General technical data                                  |                         |
| electrical input frequency                              |                         |
| • minimum                                               | 50 Hz                   |
| • maximum                                               | 50 Hz                   |
| principle of operation / of the operating hours counter | analog                  |
| reset function                                          | no                      |
| input voltage                                           | 230 V                   |
| Supply voltage                                          |                         |
| type of voltage                                         | AC                      |
| Protection class                                        |                         |
| protection class IP                                     | IP20                    |
| Number                                                  |                         |

|                                            |   |
|--------------------------------------------|---|
| number of characters that can be displayed | 7 |
|--------------------------------------------|---|

### Mechanical Design

|                               |          |
|-------------------------------|----------|
| height                        | 90 mm    |
| height / of the front plate   | 45 mm    |
| width                         | 36 mm    |
| width / of the front plate    | 36 mm    |
| installation depth            | 64 mm    |
| number of modular width units | 2        |
| fastening method              | DIN rail |
| net weight                    | 93 g     |

### Certificates

|                                                                                                           |                    |
|-----------------------------------------------------------------------------------------------------------|--------------------|
| reference code                                                                                            |                    |
| <ul style="list-style-type: none"> <li>• acc. to DIN EN 61346-2</li> <li>• acc. to IEC 81346-2</li> </ul> | <p>P</p> <p>PH</p> |

### General Product Approval

### Declaration of Conformity



UR



EG-Konf.

### Further information

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KT5804>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KT5804>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=7KT5804](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KT5804)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

<http://www.siemens.com/specifications>

