

Data manager for communication between PC U Configuration via web browser, reading out via web browser, APP (SmartPhone, tablet), CSV. and Powermanager, data memory



Model

product brand name	SENTRON
product designation	7KT PAC1200
product type designation	Data manager

General technical data

measuring precision	Total accuracy +/-1% (of full-scale value / class 1)
measured variable current / rated value	63 A

Supply voltage

line frequency / rated value	Yes
• 50 Hz	
measurable line frequency	50 +/- 5%
• full-scale value	

Current

current / at output / rated value	5 A
-----------------------------------	-----

Suitability

suitability for use	Yes
• reactive power meter	

• revolution measuring instrument	No
• frequency meter	Yes
• pulse counter	No
• voltmeter	No
• wattmeter	Yes
protocol / is supported	Modbus TCP

Measuring inputs

measurable supply voltage	
• between (PE)N and L / at AC / maximum rated value	230 V
• between the line conductors / at AC / maximum rated value	400 V

Mechanical Design

height	85 mm
depth	32.7 mm
number of modular width units	4
net weight	280 g

Certificates

Declaration of Conformity



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KT1260>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KT1260>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KT1260

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>







