



SETRON, measuring device, 7KM PAC2200, LCD, L-L: 400 V, L-N: 230 V, 5 A, strd rail instr., 3-phase, M-Bus + MID, apparent /active/reactive energy, self-powered, screw terminals

Model				
product brand name		SETRON		
product quality / calibrated		Yes		
type of measured value detection / load profile		No		
type of signal		S0		
design of the energy counter		Solid-state		
design of the pulse output		Electrical		
Supply voltage				
operating voltage				
• between L and L / minimum		3 V		
• between L and L / maximum		480 V		
• between N and L / minimum		3 V		
• between N and L / maximum		276 V		
Protection class				
protection class IP		IP40		
Current				
tariff version of the energy counter		two tariff		
short-term overload current		100 A		
Main circuit				
operating frequency / rated value				
• minimum		45 Hz		
• maximum		65 Hz		
operational current / rated value		5 A		
Suitability				
suitability for use		Import/export		
Product function				
product function				
• backstop		Yes		
• blocking code		Yes		
Display and operation				
display version		digital		
Number				
number of characters that can be displayed		12		
Mechanical Design				
number of modular width units		6		
net weight		410 g		
General Product Approval		Declaration of Conformity	Test Certificates	other

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KM2200-2EA30-1GA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KM2200-2EA30-1GA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KM2200-2EA30-1GA1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





