



SETRON, measuring device, 7KM PAC2200, LCD, L-L: 400 V, L-N: 230 V, 65 A, strd rail instr., 3-phase, Modbus TCP, apparent /active/reactive energy, self-powered, screw terminals

Model			
product brand name		SETRON	
product quality / calibrated		No	
type of measured value detection / load profile		No	
type of signal		S0	
design of the energy counter		Solid-state	
design of the pulse output		Electrical	
Supply voltage			
operating voltage			
• between L and L / minimum		3 V	
• between L and L / maximum		480 V	
• between N and L / minimum		3 V	
• between N and L / maximum		276 V	
Protection class			
protection class IP		IP40	
Current			
tariff version of the energy counter		two tariff	
short-term overload current		65 A	
Main circuit			
operating frequency / rated value			
• minimum		45 Hz	
• maximum		65 Hz	
operational current / rated value		65 A	
Suitability			
suitability for use		Import/export	
Product function			
product function			
• backstop		Yes	
• blocking code		Yes	
Display and operation			
display version		digital	
Number			
number of characters that can be displayed		12	
Mechanical Design			
number of modular width units		6	
net weight		528 g	
General Product Approval		Declaration of Conformity	other

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=7KM2200-2EA40-1EA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/7KM2200-2EA40-1EA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KM2200-2EA40-1EA1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





