

KT 200

AC CLAMP METER



- Small and handy clamp meter
- IEC61010-1 Safety Standard CAT. III 300V, CAT. II 600V
- 400A AC Clamp meter
- DMM function ACV, DCV, Ω Continuity Buzzer.



CE

	KT 200
AC A	40.00/400.0A $\pm 2.0\% \text{rdg} \pm 6 \text{dgt}$ (50/60Hz)
AC V	400.0/600V (Auto-ranging) $\pm 2.0\% \text{rdg} \pm 5 \text{dgt}$ (50/60Hz)
DC V	400.0/600V (Auto-ranging) $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$
Ω	400.0/4000 Ω (Auto-ranging) $\pm 2.0\% \text{rdg} \pm 5 \text{dgt}$
Continuity buzzer	buzzer sounds below $50 \pm 35 \Omega$
Conductor size	$\phi 30 \text{mm}$ max.
Applicable standards	IEC 61010-1 CAT. III 300V(ACA), CAT. II 600V Pollution degree 2 IEC 61010-031, IEC 61010-2-032, IEC 61326-1
Power source	R03(1.5V)(AAA) x 2 *Continuous measuring time: approx. 200 hours (Auto power save: approx. 10 minutes)
Dimensions	184(L) x 68.6(W) x 38.5(D)mm
Weight	Approx. 190g (including batteries)
Accessories	7066A (Test leads), R03(AAA) x 2, Instruction manual
Optional	9105 (Carrying case)

KT 203

AC/DC CLAMP METER



- Small and handy clamp meter
- IEC61010-1 Safety Standard CAT. III 300V, CAT. II 600V
- 400A AC/DC Clamp meter
- DMM function ACV, DCV, Ω Continuity Buzzer.



CE

	KT 203
AC A	40.00/400.0A (Auto-ranging) $\pm 3.0\% \text{rdg} \pm 8 \text{dgt}$ [50/60Hz] (0~40.00A) $\pm 3.5\% \text{rdg} \pm 6 \text{dgt}$ [50/60Hz] (15.0~299.9A) $\pm 4.0\% \text{rdg} \pm 6 \text{dgt}$ [50/60Hz] (300.0~400.0A)
DC A	40.00/400.0A (Auto-ranging) $\pm 3.0\% \text{rdg} \pm 8 \text{dgt}$ (0~40.00A) $\pm 3.5\% \text{rdg} \pm 6 \text{dgt}$ (15.0~299.9A) $\pm 4.0\% \text{rdg} \pm 6 \text{dgt}$ (300.0~400.0A)
AC V	400.0/600V (Auto-ranging) $\pm 2.0\% \text{rdg} \pm 5 \text{dgt}$ (50/60Hz)
DC V	400.0/600V (Auto-ranging) $\pm 1.5\% \text{rdg} \pm 5 \text{dgt}$
Ω	400.0/4000 Ω (Auto-ranging) $\pm 2.0\% \text{rdg} \pm 5 \text{dgt}$
Continuity buzzer	buzzer sounds below $50 \pm 35 \Omega$
Conductor size	$\phi 30 \text{mm}$ max.
Applicable standards	IEC 61010-1 CAT. III 300V(ACA), CAT. II 600V Pollution degree 2 IEC 61010-031, IEC 61010-2-032, IEC 61326-1
Power source	R03(1.5V)(AAA) x 2 *Continuous measuring time: approx. 35 hours (Auto power save: approx. 10 minutes)
Dimensions	187(L) x 68.5(W) x 38.5(D)mm
Weight	Approx. 200g (including batteries)
Accessories	7066A (Test leads), R03(AAA) x 2, Instruction manual
Optional	9105 (Carrying case)