



Bell transformer, 14VA Primary 230-240 V AC, 50 Hz, secondary 8 V, 12V, 24V AC With PTC fuse, 2MW++

Model		
product brand name		SENTRON
product designation		Bell transformer
design of the transformer		Standard bell transformer
General technical data		
supplied active power maximum		14 W
Voltage		
input voltage		230 V
output voltage		
• _1 rated value		8 V
• _2 rated value		12 V
• _3 rated value		24 V
Dissipation		
power loss [W] for rated value of the current at AC in hot operating state per pole		11 W
Current		
output current		
• maximum		2 A
• _1 rated value		2 A
• _2 rated value		1.3 A
• _3 rated value		0.6 A
Suitability		
suitability for integration		
• surface-mounted installation		No
• flush mounting		No
Product details		
product component switch		No
Product function		
product function thermal protection		Yes
Inputs Outputs		
property of the output short-circuit proof		Yes
Mechanical Design		
height		64 mm
width		36 mm
length		90 mm
number of modular width units		2
fastening method side-by-side mounting		Yes
General Product Approval		Declaration of Conformity
		other

[Confirmation](#)



[Environmental Con-
firmations](#)

[Miscellaneous](#)

other

[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AC3214-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AC3214-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AC3214-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



