




## Surface-mounted video door station, 3-gang



| Specification                                                                                        | Order No. | Packing unit | £/piece<br>without VAT | PS | EAN           |
|------------------------------------------------------------------------------------------------------|-----------|--------------|------------------------|----|---------------|
|  pure white        | 1270 66   | 1            | 1,149.92               | 10 | 4010337270669 |
|  anthracite       | 1270 67   | 1            | 1,161.86               | 10 | 4010337270676 |
|  colour aluminium | 1270 65   | 1            | 1,161.86               | 10 | 4010337270652 |

## Features

- Fully pre-assembled surface-mounted door station for vertical surface-mounted installation. This allows quick and clean installation.
- In the design of the design line Gira TX\_44.
- Torsionally rigid surface-mounted housing thanks to aluminium profile.
- Frame made of shatter-proof thermoplastic with high resistance to ultraviolet light as well as a scratch-resistant, care-free surface.
- Theft protection by means of screws with hexalobular socket.
- Signal transmission and supply of the audio and video components via reverse-polarity-protected and short-circuit-proof 2-wire bus.
- One-man start-up with easy start-up procedure.
- Weather-resistant speaker.
- High-quality electret microphone.
- Speakerphone function (voice-controlled talk-back with echo and background noise suppression).
- Acknowledgement tone when call button is pressed.
- Adjustable voice volume.
- White call-button illumination in LED technology. Even, clearly visible call button illumination is achieved via maintenance-free, energy-saving LED technology.
- Sprayed-water proof call-button cover plate made of shock-resistant plastic.
- Name plate of the call button can be exchanged without tools and without frame disassembly.
- Professional labelling is available from the Gira Inscription Service [www.marking.gira.com](http://www.marking.gira.com) or using the Gira inscription software.
- Automatic day or night switching: the camera switches from day mode (colour display) to night mode (black and white display) and back again at a defined ambient brightness. Due to the high degree of light sensitivity in night mode, good presentation results are achieved even in poor lighting conditions.
- LEDs ensure steady illumination of the field of view at close proximity in night mode.
- Camera can be manually swivelled 20° horizontally and vertically. In combination with the wide-angle lens, a very wide field of view results.

- Automatic background lighting compensation.
- Automatic white balance.
- Automatic gain control (AGC).
- Integrated camera heating with temperature detection.
- Sprayed-water proof cover plate.
- Camera cover plate made of shock-resistant plastic. Easy to replace if damaged, e.g. due to vandalism.

---

## Technical data

|                                                   |                           |
|---------------------------------------------------|---------------------------|
| Power supply:                                     | via the 2-wire bus        |
| Connections                                       |                           |
| - 2-wire bus:                                     | 2x screw terminals        |
| - Additional power supply:                        | 2x screw terminals        |
| Protection type:                                  | IP44                      |
| Ambient temperature:                              | -25 °C to +70 °C          |
| Image recording element:                          | CCD sensor 0.85 cm (1/3") |
| Wide-angle lens:                                  | 150°                      |
| Visible detection range:                          | 100°                      |
| Area of detection (for 20° swivelling):           | 140°                      |
| Colour system:                                    | PAL                       |
| Pixels:                                           | 500 (H) x 582 (V)         |
| Horizontal resolution:                            | 380 TV lines              |
| Switchover threshold for colour to B/W operation: | 1 lux                     |
| Light sensitivity in B/W operation:               | 0.1 lux                   |
| Electronic shutter speed::                        | up to 1/100000 s          |
| IR filter:                                        | integrated                |
| Recommended mounting height for camera:           | 1.50 m                    |

---

## Notes

- Call buttons which are not required can be covered with the call-button cover plate for call button, 3-gang.

---

## Dimensions in mm

|                 |       |       |      |
|-----------------|-------|-------|------|
| without camera: | W 110 | H 253 | D 19 |
| with camera:    | W 110 | H 253 | D 40 |
| Name plates:    | W 62  | H 18  | D -  |