








## TFT colour display



Specification	Order No.	Packing unit	£/piece without VAT	PS	EAN
 cream white glossy	1286 01	1	591.71	10	4010337001539
 pure white glossy	1286 03	1	591.71	10	4010337001638
 pure white matt	1286 27	1	591.71	10	4010337002550
 anthracite	1286 28	1	595.41	10	4010337002567
 colour aluminium	1286 26	1	600.20	10	4010337002543
 black matt	1286 005	1	600.20	10	4010337038047
 stainless steel	1286 600	1	616.10	10	4010337021025

## Features

- High-resolution, active TFT colour display for extension of the home stations.
- Uniform installation of door communication and electrical installation in a device box.

- Design diversity thanks to integration in the design line. This facilitates the uniform appearance of the door communication and electrical installation.
- Signal transmission and supply of the audio and video components via reverse-polarity-protected and short-circuit-proof 2-wire bus.
- Because of modularity, simple extension of the home stations with the TFT colour display.
- Colour display with LED backlighting.
- OSD function, i.e. text presentation in display for status display and menu guidance.

1-way switch with the following functions

- Manual switching on/off of TFT colour display.
- Camera changeover – targeted selection of up to 15 camera sources. Text in the display indicates which camera is currently being controlled.

Cursor buttons with 5-way-navigation for parameter setting

- As end customer: brightness, colour intensity, contrast, switch-on time of the display.
- As installer: selection of the language (German or English), frequency setting, termination of the cable, display of version, factory setting, switching display on or off, switching LED illumination on or off, brightness, colour intensity, contrast, and switch-on time of the display.

---

## Technical data

Power supply:	via connection cable
Display insert connections	
- Connection cable:	2 x connector strip
- Video:	1 x connector strip
Colour system:	PAL
Display size	
- System 55:	4.57 cm (1.8")
- Gira F100:	6.35 cm (2.5")
Number of pixels	
- System 55:	557 x 234
- Gira F100:	960 x 240
Installation depth:	33 mm.
Ambient temperature:	-5 °C to +50 °C

---

## Notes

- Cannot be used in combination with the surface-mounted home station.
  - Integration possible in Profile 55.
-