

GlassProtect

Small wireless detector that notifies of glass being broken by intruders. It is installed at a distance of 9 m from the window and filters events that cause false alarms about breakage.

- Authentication to prevent forgery
- Jamming detection and communication channels encryption
- Tampering alarm

| | | |
|--|--|---|
| Operates up to 7 years without battery replacement | Ignores thunder, dogs barking and noise outside the window | Detects breakage at a distance of up to 9 m |
|--|--|---|

Principle of operation

Detects broken glass using an electret microphone, which registers the sound of impact against the glass and of the glass falling.

Features

Two-factor detection of broken glass prevents false alarms caused by thunder, dogs barking and noise from passing trucks.

Installation and set up

Ready to operate straight out the box: the battery is already installed, therefore there is no need to disassemble the detector. With one click, it can be connected to the hub in the mobile application. It can be mounted on the SmartBracket in just a few minutes.

Tech specs

| | |
|----------------------------|--|
| Classification | Surface sound radio channel security detector |
| Type of detector | Wireless |
| Installation method | Indoors |
| Compatibility | Operates only with Hub , Hub Plus , ReX , ocBridge Plus , uartBridge |
| Sensing element | Electret microphone |
| Break detection distance | Up to 9 m |
| Alarm signal delivery time | 0.15 s |

| | |
|-----------------------------|---|
| Sensitivity | Adjustable, 3 levels |
| Detection angle | 180° |
| Power supply | Battery: CR123A battery Power supply voltage: 3 V Battery life — up to 7 years |
| Jeweller radio technology | Communication range with central unit — up to 1,000 m in an open space Two-way communication between devices Operating frequencies — 868.0-868.6 MHz Self-adjusting RF output power — up to 20 mW Block encryption based on AES algorithm Detector polling period — 12–300 s Learn more about Jeweller > |
| Temperature sensor | Available |
| Operating temperature range | From -10°C to +40°C |
| Permissible humidity | Up to 75% |
| Anti-sabotage | Protection against fraud Jamming detection Tamper-resistant |
| Remote setting and testing | + |
| Dimensions | Diameter: 20 mm Height: 90 mm |
| Weight | 30 g |
| Certification | Grade 2, CE |
| Warranty | Replacement and repair within 24 months of the date of sale. Batteries are not covered under warranty. Learn more > |
| Complete set | GlassProtect glass break detector SmartBracket mounting panel CR123A battery (pre-installed) External contact Installation set User's guide |