



SCS6U Keystone jack, U/UTP unscreened, Category 6, Tool-less, 180 degrees (GSCAT6AU24)







Standards of reference and applications

Standards: IEC60603-7-5, ISO/IEC 11801, IL/cUL Safety Standards, EIA/TIA 568b.2-1, EN 50173

Applications: 1000BASE-T Gigabit Ethernet, 100BASE-TX Fast Ethernet, 10 Base-T Ethernet, 622Mbps ATM, 155Mbps ATM

Features

Standard RJ45 footprint
Fast, easy, reliable termination
Clear IDC termination colour coding
Suitable for unscreened cables
Available as multiple colours
25 Years System Warranty
Wiring Specifications T568A & T568B

Installation Features

Store at -40 to +60 °C Install at -0 to +50 °C Operate at : -40 to +60 °C Fitting : keystone jack

Design

 $\textbf{Dimensions}:\ 17.59\ x\ 32.16\ x\ 26.94mm$

Housing: High-impact Flame Retardant Polycarbonate, UL94V-0 Spring Wire: Phosphor Bronze With Gold-plated 3u-50u

IDC Contact : Phosphor Bronze
Insertion life : ≥1000 mating cycles

IDC Accept: 22-26 AWG
Wire Scheme: T568A/B
Insulation Resistance: 500Ω
Current Rating: 1.5Amps
DC Resistance: 0.1 ohm MAX
Voltage: 150 VAC MAX
Plug Retention Force: 89N
Pack: 24pc/box – 960pcs/box

APS

HIGH TECHNOLOGY CABLES & CONNECTIVITY SOLUTIONS

Round cable outer diameter: 5.0 - 8.0 mm

Flat cable outer diameter: NO

Tool: no tool
Cable tie: 1 pc

Ordering and delivery information

P/N	Weight	Retail Packaging	Wholesale Packaging	Electric Number	GTIN
GSCAT6AU24	6.25 g	24 pcs/box 200x100x35 mm 0.2kg	960 pcs/box 34x32x45 cm 9 kg 17280 pcs/pallet 110x110x102 cm 175 kg	72 058 77	6410072058771

Edit

Recommended connectivity

	100	T	1.0		1,0/
	APS		Kerman		Warranty
Indoor Cable U/UTP Cat.6 4PR HF 305M	W5UX042M0S30	02 103 00	K6U4E3	02 070 23	included
Indoor Cable U/UTP Cat.6 4PR HF 500M	W5UX042M0B50	02 078 01	K6U4E5	02 070 24	included
Indoor Cable U/UTP Cat.6 2X4PR HF 305M	W5UX08TM0B50	02 103 18	K6U8E5	02 070 26	included
Outdoor Cable U/UTP Cat.6 4PR PE 500M	-	-	KU64E5	02 070 27	included
Indoor/Outdoor Cable U/UTP Cat.6 4PR LSZH/PE 500M	W5UX042WEB50	02 103 17	-	-	not included
Patch Panel	PPE24SU	72 265 11	KRM24H	72 094 07	included
Patchcords	6URT45-	-	6URT45-	-	not included
Field Connector RJ45 (tool-less)	-	-	KRJ45U- U	72 477 00	not included

Edit

Extended System Warranty

The APS System Warranty assures the compliance of the system performance to the applicable class of cabling for a period of 25 years. The warranty may be applied for by an accredited APS Partner who has designed and/or installed the entire system.



Every effort has been put so that this document is most reliable and free from errors. However, AP Solutions Oy cannot be considered responsible for any mistake in this document and users should consult AP Solutions Oy for any information needed. AP Solutions Oy reserves the right to make changes to the documents at any time, without prior notice.