

# CCHE Panel, LC duplex CCHE Panel, LC duplex

The Corning logo is a blue square with the word "CORNING" in white, uppercase, sans-serif font.

## **Part Number: CCHE-CP12-AD**

The panels are used with field-installable connectors or in applications where the preconnectorized cables are routed directly from the equipment to the piece of inter-connect hardware. This provides an efficient way to securely mate two or more connectors.

Closet connector housing panels are offered in 6-, 8-, 12-, 16- and 24-fiber panels for use with the LANscape® solutions hardware products. The panels are used with field-installable connectors or in applications where the pre-connectorized cables are routed directly from the equipment to the inter-connect hardware. The panels are available with a variety of industry-standard adapter types. In most applications, the closet connector housing panels are designed for applications where specified labeling and connector identification are required. This is accomplished by the use of colored icons with different symbols molded into the icon.

## Features and Benefits

Designed to accommodate all industry-standard adapter types

---

Unique colour-coded connector labeling system

---

Universal approach is used; one panel size fits in all standard LANscape® Solutions hardware

---

Available in 6-, 8- and 12-fiber count options in most adapter styles; 16- and 24-fiber count options available in MT-RJ and LC duplex styles

---

Also available for copper modules 12-fibre ST® Compatible Connector Panel, 12-fibre SC Duplex Panel, 24-fibre MT-RJ Connector Panel; 36-, 72- and 144-fibre count options available only with MTP® adapters

# CCHE Panel, LC duplex CCHE Panel, LC duplex

CORNING

## Specifications

### Design - Adapter

Adapter Housing Color	Aqua
Adapter Housing Material	Composite
Keyed adapter	No
Shuttered adapter	Yes
Adapter Type	LC duplex shuttered
Insert Material	Ceramic

### Design

Fiber Count	12
Color	Black
Number of Adapters	6
Housing Material	High-grade steel

### General Specifications

Fiber Category	50 µm MM (OM3/OM4)
----------------	--------------------

### Cable Design

Fiber Count	12
-------------	----

### Shipping Dimensions

Height	250 mm
--------	--------

# CCHE Panel, LC duplex CCHE Panel, LC duplex

CORNING

## Shipping Dimensions

Width	190 mm
-------	--------

Depth	180 mm
-------	--------

## Dimensions

Length	155 mm
--------	--------

Width	35 mm
-------	-------

## Ordering Information

Weight	0.06 kg
--------	---------

Shipping Weight	0.3 kg
-----------------	--------

Units per Delivery	1/1
--------------------	-----



Corning Optical Communications GmbH & Co. KG • Leipziger Strasse 121 • 10117 Berlin, Germany  
+00 800 2675 4641 • FAX: +49 30 5303 2335 • [www.corning.com/opcomm/emea](http://www.corning.com/opcomm/emea)