

**Uniprise Solutions**

760163527 | HFTP-J10G

Uniprise Ultra 10® HFTP-J10G Shielded High Density Information Outlet

Dimensions

Depth	33.53 mm		1.32 in
Height	19.56 mm		0.77 in
Width	17.02 mm		0.67 in

Electrical Specifications

ANSI/TIA Category	6A
Contact Resistance Variation, maximum	20 mOhm
Contact Resistance, maximum	100 mOhm
Current Rating	1.5 A @ 20 °C 1.5 A @ 68 °F
Dielectric Withstand Voltage, RMS, conductive surface	1500 Vac @ 60 Hz
Dielectric Withstand Voltage, RMS, contact-to-contact	1000 Vac @ 60 Hz
Insulation Resistance, minimum	500 MOhm

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Relative Humidity	Up to 95%, non-condensing
Safety Standard	cUL UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Cable Type	F/UTP (shielded) S/FTP (shielded)
Color	Silver
Brand	Uniprise®
Application	Adapts to M-Series and Keystone
Package, quantity	25
Product Type	Outlet

Mechanical Specifications

Conductor Gauge, solid	22 AWG 24 AWG
Conductor Gauge, stranded	22 AWG 24 AWG
Conductor Type	Solid Stranded
Material Type	Copper alloy High-impact, flame retardant, thermoplastic Zinc
Outlet Type	High density
Outlet/Module Contact Plating	Precious metals

760163527 | HFTPJ10G

Plug Insertion Life, minimum	750 times
Plug Insertion Life, test plug	IEC 60603-7 compliant plug
Plug Retention Force, minimum	30 lbf 133 N
Rear Termination Contact Plating	Nickel
Rear Termination Type	IDC
Wiring	T568A T568B


Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system



Included Products

760154187 | HGS-A-MS-WHITE — High Density M-Series Adapter, white



760154187 | HGS-A-MS-WHITE
High Density M-Series Adapter, white

Dimensions

Depth	9.14 mm		0.36 in
Height	17.53 mm		0.69 in
Width	18.54 mm		0.73 in

Environmental Specifications

Flammability Rating	UL 94 V-0
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Safety Standard	cUL UL
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)

General Specifications

Product Type	Adapter
Color	White
Brand	SYSTIMAX®
Ordering Note	Minimum order quantity, 20 packs
Package, quantity	25

Mechanical Specifications

Material Type	High-impact, flame retardant, thermoplastic
---------------	---

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

