





Specially designed to meet (according to their classification) with the requirements of some premises (e.g.: industry, warehouse, parking...).

The IPBOX is characterized by the degree of protection it provides against dust (no harmful deposit) and against low-pressure water jets sprayed from any directions, according to IEC 60529.

- Available with safety glass door with metal frame or full metal door.
- Door with hot-poured polyurethane gasket.
- Two locking points to ensure uniform pressure of the door gasket on the cabinet frame.
- Key lock type "butterfly button" for better ergonomics handling.
- Cables entry plates (top and bottom) with hot-poured polyurethane gasket, screw fixing.
- Delivered with wall mounting brackets.
- A pole mounting bracket is also available (sold separately).

A very high-quality product, both in terms of design that finish. It will meet the most stringent requirements.

• Type: single section

- Design: steel, assembly by welding
- 19" mounting profiles: 2 adjustable in depth 19" mounting profiles
- Front door: reversible full metal door, can be opened up to 180°, locked by using key locks (N°333)
- · Cables entries: on the top and the bottom
- Height: 871 mm
- Width: 600 mm
- Depth: 500 mm
- Capacity: 18 U
- Colour: RAL 7035 (light grey)
- Protection class: IP55
- Load capacity: 60 kg
- Delivered with earthing kit and wall mounting brackets