



## 19" Servers floor standing cabinet GIGARACK Type 250 2 colocation parts 42 U 800 x 1000

**GGM ALSC2C42810A**



The rigidity and the load capacity of the aluminium frame, the high level of equipment, finishing, the aesthetic... to summarize, a added value product !

The screws assembly design of the frame allows a complete disassembly of the cabinet, very convenient in case of difficult access.

The features / price ratio which makes it one of the added value product of the market.

A server needs a supply of cold air in the front to optimise dissipation of the heat it produces.

Then, the heated air is expelled by the rear of the server.

To achieve this process of cooling, it is essential to have a cabinet equipped with front and rear perforated doors to allow the air flow to circulate thus avoiding any risk of overheating.

- Type : Server colocation
- Frame : Aluminium, assembly by screws
- 19" monting profiles : 4 adjustable in depth 19" mounting profiles independent per compartment, "U" marking, 9,5 x 9,5 mm cage nut size holes
- Front door : Reversible perforated door, can be opened up to 190°, locked by using swing handle with key lock
- Rear door : Reversible perforated door, can be opened up to 190°, locked by using swing handle with key lock
- Sides panels : 2 removable panels per compartment, locked by using latches and key locks
- Top : Full sheet with sides pre-cuts for cables entry
- Bottom : Full sheet with sides pre-cuts for cables entry
- Perforated sheet to separate each compartment
- Sides cables trunking to manage the cables inside the cabinet (serving the compartments independently)
- Support : Adjustable feet
- Height : 2020 mm
- Width : 800 mm
- Depth : 1000 mm
- Capacity : 2 x 20 U
- Color : RAL 9005
- Load capacity : 1500 kg
- Earthing kit included
- Different key sets per compartment