

SCS6U RJ45 Keystone jack, UTP unscreened, Category 6, Tool-less, 18 degrees

AKLRJ456U, Rev. 1, Date 2 2 - 9-24



Description



Standards of reference and applications

Standards

ANSI/TIA-568-C.2, ISO/IEC 11801, UL 1863, IEC 60512-99-002

Applications

Ethernet cabling, UTP Cat.6, EN50173-1 Class E, 250MHz 1GbE Provides either T568A or T568B wiring configuration Available in CAT5e and CAT6 performance levels Compatible with cable dimensions from 6-8mm; 23-26AWG

Features

Standard RJ45 footprint Fast, easy, reliable termination Clear IDC termination colour coding Suitable for unscreened cables Available as multiple colours Wiring specifications T568A & T568B

Installation features and instructions

Store at -40 to +70 °C Install at -10 to +70 °C Operate at : -10 to +70 °C Fitting : keystone jack

Download installation instructions.

Design

Dimensions : 49,7×13,9×15,4 mm Housing : High-impact Flame Retardant Polycarbonate, UL94V-0 Spring Wire : Phosphor Bronze With Gold-plated 50μm IDC Contact : Phosphor Bronze With Tin-plated 100 μm Insertion Life : ≥1000 mating cycles IDC Accept : 23-26 AWG Wire Scheme : T568A/B Insulation Resistance @ 100 VDC : 5000 MΩ Round cable outer diameter : 6,0 – 8,0 mm Dielectric Strength (VDC/VAC, 1min) : 1000 PoE : 4PPoE, 90W

Ordering and delivery information

| P/N | \$ Dimensions | \$ Retail Packaging 🖨 | Wholesale Packaging | Electric Numbe ¢ | GTIN |
|-----------|-------------------|----------------------------------|---|-------------------------|---------------|
| AKLRJ456U | 49,7x13,9x15,4 mm | 1 kpl 170x105X15 mm 0,1 kg | box: 70 kpl 248x188x209 mm 1,1 kg | 72 493 26 | 6410072493268 |

Recommended connectivity

| | APS | | Kerman | | System warranty |
|--|---------------|-----------|--------|-----------|-----------------|
| Keystone jack (single press) | - | - | GT6 | 72 093 16 | not included |
| Keystone jack (toolless) | GSCAT6AU | 72 058 68 | CM6 | 72 094 39 | not included |
| Indoor Cable U/UTP Cat.6 4PR HF 305M Dca | W5UX042M0S30 | 02 103 00 | K6U4E3 | 02 070 23 | not included |
| Indoor Cable U/UTP Cat.6 4PR HF 500M Dca | W5UX042M0B50 | 02 078 01 | K6U4E5 | 02 070 24 | not included |
| Indoor Cable U/UTP Cat.6 2X4PR HF 305M Dca | W5UX08TM0B50 | 02 103 18 | K6U8E5 | 02 070 26 | not included |
| Hybrid Cable U/UTP Cat6 4PR HF + 4xOS2 500M Dca | SCA34642A0 | 02 078 04 | KH64D5 | 02 073 12 | not included |
| Hybrid Cable U/UTP Cat6 4PR HF + 4xOS2 500M Cca | SCA34642A0CCA | 02 331 00 | - | - | not included |

| | APS | | Kerman | | System warranty |
|--|--------------|-----------|--------|-----------|-----------------|
| Outdoor Cable U/UTP Cat.6 4PR PE 500M | - | - | KU64E5 | 02 070 27 | not included |
| Indoor/Outdoor Cable U/UTP Cat.6 4PR LSZH/PE 500M | W5UX042WEB50 | 02 103 17 | - | - | not included |

Every effort has been put so that this document is most reliable and free from errors. However, AP Solutions Oy cannot be considered responsible for any mistake in this document and users should consult AP Solutions Oy for any information needed. AP Solutions Oy reserves the right to make changes to the documents at any time, without prior notice.