

Mechanical Gel Housing

miniClosure Size 2: 4 Ports up to 12 mm

CORNING

Gel filled protection housing for round or flat low pair copper cables. Installation in manholes, direct burial, aerial or on walls and poles.

This protection housing is a miniature closure for copper connections. It allows realizing straight or branch connections. Incoming and outgoing cables are fixed with 2 cable ties. Lower and upper shells of the closures are filled with gel that covers the splice entirely. The gel is not water-soluble and guarantees a reliable long term sealing in every environment.

Features

- Simple and quick installation without special tooling or additional heating
- Standard cable preparation
- Cables are held with cable ties at the cable entrances in place
- Can be used with different connector types
- Gel sealing
- Locking with 6 clips
- Weather- UV- and water resistant
- Wall mounting possibility integrated



Standards

Approvals and Listings Protection class: IP 68
Meets Telcordia GR 3151
Core

Specifications

Design - Hardware	
No. of pairs	1 to 10
Cable entrance	4 Ports up to 12 mm
Dimensions (HxWxD)	50 mm x 80 mm x 150 mm

Mechanical Gel Housing

miniClosure Size 2: 4 Ports up to 12 mm

CORNING

Mechanical Characteristics

Pulling force	4.5 kg
---------------	--------

Ordering Information

Part Number	MINICLS2-WW-02
Product Description	Mechanical Gel Housing, miniClosure Size 2: 4 Ports up to 12 mm

Shipping Information

Units Per Delivery	2/1
--------------------	-----



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY

00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified.

© 2017 Corning Optical Communications. All rights reserved.