



HIGH CRUSH RESISTANCE

With small diameter, Simplex/Duplex 3.0mm 12F 3.5mm, 24F 5mm and dual strength member (FRP and Kevlar) EZ-T is suitable for FTT Drop, In-Home wiring and Data Center Multi ber assembly





Available

with G.652D, G.657A1, A2 and A3 and OM1, OM2, OM3 and OM4 ber



Available

with Riser, Plenum, LSZH material and different color jacket



Extra Small & Ultra light

weight cable with 1 to 48 ber count



High crush resistance

up to 200Kgs per GR-409



High Tensile strenath

without conductive material



Great bending performance

less than 0.1dB macrobending loss at 1550nm with 10mm radius with G.657A2 ber



www.senko.com

2F 3.0 mm 0.D.






Cable 12F 3.5mm 0.D.






24F 5.0 mm 0.D.

5.0



Bending Corners and Loading Test

3mm EZ-T Simplex Cable with G.657A1 fiber tested with 40 of 90 degree corners, staples and 15kgs weight and total loss at 1550nm was less than 0.1dB with In page 7, we putthecable around 40 corners and hang up 15kg weight on one end of cable to test the loss change.



BENEFITS



• 12F/24F type is ideal for Data Center **Application**



• Easy installation even in over populated duct without twist and kink.



• Ideal for in-house wiring, under carpet, stapling etc.



Suitable for factory termination and field installable connectors

SENKO ADVANCED COMPONENTS, INC.

Americas

USA EAST 1-888-32-SENKO USA WEST 1-858-623-3300 Sales-Americas@senko.com

HONG KONG +852-2121-0516 SHANGHAI +86-21-5830-4513 SHENZHEN +86-755-2533 -4893 POLAND +48-71/77-60-737 Sales-Asia@senko.com

Europe

UK +44 (0) 118 982 1600 ITALY +39 011 839 9828 Sales-Europe@senko.com Asia Pacific AUSTRALIA +61 (0) 3 9755-7922 Sales-Asia-Pacific@senko.com

Middle East North Africa Dubai +971 4 8865160 Sales-MENA@senko.com

Japan TOKYO +81-(0)3-5825-0911 Sales-Japan@senko.com

CALL 1-888-32-SENKO