

TECHNICAL DATA SHEET OF .08 GROUNDING KIT



SPECIFICATIONS

- Shell:**
Rubber EPDM and
Stainless steel AISI 304.
- Screws:**
Stainless steel AISI 304.
- Connection cable:**
Flexible copper wire,
insulation black.
- Cable lugs:**
Tinned copper. Lug hole Ø 8mm
- Contact:**
Tinned copper.
- Contact resistance:**
10 mΩ
- Operation temperature**
-40 - +85°C
- Surge current:**
70KA at waveform 8/20μs
- Waterproof test:**
IP 68
- Test standard:**
MIL-STD-1757A

NKC Code	For cables	Grounding cable Length [m]	Product marking	Tool	 Pc.
NKG101200.08	RFA, RF, RFF and RFX ½"	0.6	AFJDK02-39	NKA1401222	283g
NKG107800.08	RFA, RF, RFE and RFX 7/8"	0.6	AFJDK02-36	NKA1407822	300g
NKG107802.08	RFA, RF, RFE and RFX 7/8"	1.2	AFJDK02-35	NKA1407822	400g
NKG111400.08	RFA, RF, RFE and RFX 1 ¼"	0.6	AFJDK02-38	NKA1411422	324g
NKG115800.08	RFA, RF, RFE and RFX 1 5/8"	0.6	AFJDK02-37	NKA1415822	340g