

AP / UP-K Wall outlet IP44

surface / duct mounted
for 2 modules, with key lock



Surface mounted (AP) version



Duct mounted (UP-K) version

DESCRIPTION

Structured premises cablings in the industrial sector, for the transmission of Ethernet protocols.
Wall outlet IP44, surface or duct mounted, for 2 modules.

Suitable for the following Datwyler modules:

- PS-GG45 7_A shielded
- RJ45 module MS-K 1/8 Cat. 6/E_A shielded
- RJ45 module MS-K Plus 1/8 Cat. 6_A shielded
- RJ45 module MS-C6_A 1/8 Cat.6_A shielded
- RJ45 module KS-T 1/8 Cat. 6/E_A tool-less shielded
- RJ45 module KS-TS 1/8 Cat. 6/E_A tool-less shielded
- RJ45 module KS-T Plus 1/8 Cat. 6_A tool-less shielded

For information on the properties of the module: see data sheet of the requested module.

Lockable outlet with protection rating IP44.

Cover can also be locked with connected patch cords.

One-key system.

Cable entry from the top (one or two cables).

Shatter-proof, stable housing, grey, similar to RAL 7035.

Delivery without modules.

DIMENSIONS

Surface mounted version: W x H x D = about 90 x 93 x 90 mm

Duct mounted version: W x H x D = about 90 x 93 x 32 mm

VERSIONS

Article Number	Product	Colour (similar to)	PU
417500	UP-K Wall outlet IP44, duct mounted, for 2x MS/MU 1/8 (delivery without modules)	light grey, RAL 7035	1 pc.
417501	AP Wall outlet IP44, surface mounted, for 2x MS/MU 1/8 (delivery without modules)	light grey, RAL 7035	1 pc.
417503	AP Wall outlet IP44, surface mounted, for 2x Keystone module (delivery without modules)	light grey, RAL 7035	1 pc.