



ACS 2 - 2 way splitter

Article number: 343242

Product description:

ACS 2 - 2 way splitter

Triax splitter all round performance for use in CATV, SMATV & MATV

- Frequency range 5-1000 MHz
- High shielding
- Return loss Grade 2
- High quality die cast housing Sn coated
- All ports AC/DC blocked at inner conductor
- Acc. to EN 50083-2 & EN 60728-4

Specifications

ORDER INFORMATION	
EAN Number	5702663432420
SHIELDING	
Shielding efficiency VHF/UHF	> 110 dB
CHARACTERISTICS	
Type	COAX splitter
FREQUENCY	
Frequency range	5...1000 MHz
LOSS	
Tap loss (in-tap) 40-470 MHz	3.6 dB
Tap loss (in-tap) 470-860 MHz	3.6 dB
Tap loss (in-tap) 5-40 MHz	3.5 dB
Tap loss (in-tap) 860-1000 MHz	4.0 dB
ISOLATION	
Isolation (tap-tap) 40-470 MHz	32 dB
Isolation (tap-tap) 470-860 MHz	28 dB
Isolation (tap-tap) 5-40 MHz	30 dB
Isolation (tap-tap) 860-1000 MHz	28 dB
RETURN LOSS	
Return loss (in-out) 40-470 MHz	21 dB
Return loss (in-out) 470-860 MHz	21 dB
Return loss (in-out) 5-40 MHz	22 dB
Return loss (in-out) 860-1000 MHz	20 dB
Return loss (tap) 40-470 MHz	21 dB
Return loss (tap) 470-860 MHz	21 dB

Return loss (tap) 5-40 MHz	22 dB
Return loss (tap) 860-1000 MHz	20 dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
Certification	CE, RoHS, EN 60728-4
Screening Efficiency	EN50083-2 (Class A)
CONNECTORS	
Connector Type	F-female
Number of outputs	2
MECHANICAL	
Packaging Depth	0,030 m
Packaging Height	0,060 m
Total Weight	0,045 kg
Packaging Width	0,070 m
Main Material	Zinc die-casting bright tin plated
Net Weight	0,040 kg
Packing QTY	1
Tara Weight	0,005 kg
Bracket (optional)	1x ACB-S / Art No 343232