



ACV 4 - 4 way splitter

Article number: 343252

Product description:

ACV 4-4 - 4 way splitter, one-sided connectors

Triax splitter all round performance for use in CATV, SMATV & MATV

- Frequency range 5-1000 MHz
- High shielding
- Return loss Grade 2
- High quality die cast housing Sn coated
- All ports AC/DC blocked at inner conductor
- Acc. to EN 50083-2 & EN 60728-4

Specifications

ORDER INFORMATION	
EAN Number	5702663432529
SHIELDING	
Shielding efficiency VHF/UHF	> 110 dB
CHARACTERISTICS	
Type	COAX splitter
FREQUENCY	
Frequency range	5...1000 MHz
LOSS	
Tap loss (in-tap) 40-470 MHz	7.2 dB
Tap loss (in-tap) 470-860 MHz	8.0 dB
Tap loss (in-tap) 5-40 MHz	6.8 dB
Tap loss (in-tap) 860-1000 MHz	8.2 dB
ISOLATION	
Isolation (tap-tap) 40-470 MHz	30 dB
Isolation (tap-tap) 470-860 MHz	27 dB
Isolation (tap-tap) 5-40 MHz	27 dB
Isolation (tap-tap) 860-1000 MHz	27 dB
RETURN LOSS	
Return loss (in-out) 40-470 MHz	22 dB
Return loss (in-out) 470-860 MHz	22 dB
Return loss (in-out) 5-40 MHz	22 dB
Return loss (in-out) 860-1000 MHz	22 dB
ELECTRICAL	
Impedance	75 Ω

OPERATIONAL	
Certification	CE, RoHS, EN 60728-4
DC Passthrough	NO - DC blocked at inner conductor
Screening Efficiency	EN50083-2 (Class A)
CONNECTORS	
Connector Type	F-female
Number of outputs	4
MECHANICAL	
Packaging Depth	0,040 m
Packaging Height	0,030 m
Total Weight	0,157 kg
Packaging Width	0,080 m
Product Length	71 mm
Main Material	Zinc die-casting, bright tin plated
Net Weight	0,150 kg
Packing QTY	1
Tara Weight	0,007 kg
Product Width	35 mm
Product Height	17 mm
Bracket (optional)	2x ACB-V / Art No 343236
