

Item no.		33026654-01		Connector type		SR TL244-TL232	
				For cable 1		NK-Cables MCUM 1,1/7,3	
				For cable 2		Draka Coax 6 CT 15 A (FRNC)	
Frequency Range		0.3 - 3000 MHz		Product photo			
Impedance (Nom.)		75 Ω					
Amp. Rating (measured)		14.0 A @10°C increase					
(calculated)		19.7 A @20°C increase					
Transfer Impedance (CoMeT)		Class A +					
		<2.5 mΩ/m @ 5-30MHz					
		<0.19 mΩ/item @ 5-30MHz					
Screening Attenuation(CoMeT)		Class A + +					
		>105 dB @ 30-1000MHz					
		>105 dB @ 1000-2000MHz					
		>95 dB @ 2000-3000MHz					
Return Loss (IEC 61169-1)		Better than		Typical		Insertion Loss Max.	
0.3 - 500 MHz		-32 dB		-35.4 dB		0.3 - 500 MHz	
500 - 860 MHz		-29 dB		-31.6 dB		500 - 860 MHz	
860 - 1000 MHz		-28 dB		-30.4 dB		860 - 1000 MHz	
1000 - 1750 MHz		-26 dB		-28.6 dB		1000 - 1750 MHz	
1750 - 2150 MHz		-26 dB		-28.6 dB		1750 - 2150 MHz	
2150 - 3000 MHz		-26 dB		-28.6 dB		2150 - 3000 MHz	
Temperature				Intermodulation		IM3	
Installing		-5° to +50° C		3rd Order (@2x+30dBm)		-130 dBc	
Operating		-40° to +70° C					
Storing		-40° to +70° C		Inner Conductor Resistance			
				(@ 1 A DC)		<4.0 mΩ	
Sealing Test				Insulation Resistance			
(IEC IP-code)		IP X8 30 meter / 8 hours		(@ 500 VDC)		>200 GΩ	
O-rings		EPDM		Dielectric Strength			
				DC Test Voltage		>3.0 kV	
Base Material				Max. Tensile Strength			
Body Parts		Brass CuZn39Pb3		Overall		>500 N	
Inner Conductor		Brass CuZn39Pb3		Inner Conductor		>200 N	
Plating				Torsional Strength			
Body Parts		Nitin-6		(Connector / Cable)		* NATM	
Inner Conductor		Nitin-6					
Insulators		COC (Topas) / PP with Glass		Test performed by		Sven-Erik Sandberg	
				Date of release		February 13, 2015	
Remarks		* Not Able To Measure(NATM): The cable starts to twist without the connector loosening its grip.					

All tests performed using instruments calibrated in accordance to our ISO 9001 certification. Further technical specifications and installation instructions can be obtained on request.