

INDOOR TAPS

5-1000 MHz F connector

PRODUCT RANGE

Ref. DeSCRIPTION

1 Way

4516 8 dB

4517 11 dB

4518 14 dB

4519 17 dB

2 Ways

4560 4 dB terminal

4561 9 dB

4562 11 dB

4563 14 dB

4564 17 dB

4565 20 dB

4566 23 dB

4567 26 dB

4 Ways

4571 8 dB terminal

4572 11 dB

4573 14 dB

4574 17 dB

4575 20 dB

4576 23 dB

4577 26 dB

8 Ways

4578 12 dB terminal

4581 20 dB

This passive line for interior distribution provided with F connectors includes taps with 1,2, 4 and 8 ways, as well as a support for wall mounting.



▲ 4578



▲ 4571



▲ 4560

References	1D	4516	4517	4518	4519
Frequency range	MHz	5-1000			
Tap losses	dB	8	11	14	17
Through losses		2.4	1.5	1.5	1.3
Rejection between taps		30	33	35	37
Dimensions	mm	52x50x20			

References	2D	4560	4561	4562	4563	4564	4565	4566	4567
Frequency range	MHz	5-1000							
Tap losses	dB	4.5	8	11	14	17	20	23	26
Through losses		-	2.5	2.0	2.0	1.5	1.0	1.0	1.0
Rejection between taps		28	28	27	27	27	27	27	27
Dimensions	mm	52x50x20							

References	4D	4571	4572	4573	4574	4575	4576	4577
Frequency range	MHz	5-1000						
Tap losses	dB	8	11	14	17	20	23	26
Through losses		-	4.0	2.5	2.0	1.0	0.5	0.5
Rejection between taps		25						
Dimensions	mm	66x56x20						

References	8D	4578	4581
Frequency range	MHz	5-1000	
Tap losses	dB	12	20
Through losses		-	<2
Dimensions	mm	92x56x20	

System accessories

4061 F type 75 ohms load DC blocked

4058 F type DC 75 ohms load