

1405 Pioneer St., Brea, CA 92821 888.975.1368 | info@kanexpro.com

4K HDMI 2-Port Splitter

1x2 HDMI Splitter with 4K Cinema resolutions

MPN: SP-HD1X24K



The KanexPro 1x2 HDMI
Splitter is a 4K@30Hz compliant
distribution amplifier lets you
duplicate one HDMI source to
2 displays without losing signal
integrity and resolution.

The Ultra HD 4K format on the HDMI splitter ensures astounding picture quality, four times the resolution of high-definition 1080p at 30 Hz. This HDCP compliant splitter is also backward compatible with previous HDMI revisions, supporting 1080p / 720p HDMI video resolution devices. Even if you don't require 4K video today, it ensures you'll be ready to take advantage of tomorrow's display technology.



FEATURES

- Distribute high-resolution HDMI signals to 2 Ultra HD displays
- Supports full 3D and 4Kx2K resolution
- Supports full HD 1080p (1920 x 1080@60Hz)
- Computer resolution up to WUXGA (1920 x1200@60Hz)
- HDCP & CEC compliant Supports

- Supports latest HDMI High Speed Specifications
- 12-bit per channel (36-bit all channel) Deep color
- Compact metal enclosure

SPECIFICATIONS

Signal Inputs/Output:

Input DDC Signal: 5 volts p-p (TTL) Maximum Single Link Range: 4K x 2K

Output Video: HDMI 1.4 with full 3D and 4Kx2K@30Hz

+ HDCP

CEC - Pass through enabled

Operating Frequency:

Vertical Frequency Range: 50/60Hz Video Amplifier Bandwidth: 2.97 Gbps

Resolutions (HDTV):

Interlaced (50&60Hz): 480i, 576i, and 1080i Progressive (50&60Hz): 480p, 576p, 720p, 1080p, and 4Ky2K

Power Requirements:

External Power Supply: 5V DC@ 1A Power consumption (Max): 5W

Units:

Size: (L-W-H): 2.51"x 2.36"x0.78" Weight: 0.66 lbs. (300g)

Environment:

Operating Temperature: 0° C ~ 40° C / 32° F ~ 104° F Storage Temperature: -20° C ~ 60° C / -4° F ~ 140° F

Limited Warranty: 1-Year Parts & Labor

Package Contents:

HDMI splitter

5V USB to DC Power Supply

Operation Manual

