

- NOTES:**
1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL ELECTRICAL CODES.
 2. REFER TO PRODUCT DOCUMENTATION FOR ADDITIONAL DETAILS PRIOR TO INSTALLATION AND PREPARATION WORK.
 3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS [INCHES].
 4. NET WEIGHT OF UNIT IS 5.57kg [12.28 lb].
 5. LENGTH OF INPUT CORD IS 3.05 Meter [120.1 Inch].


THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF SCHNEIDER ELECTRIC AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM SCHNEIDER ELECTRIC. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

Schneider Electric


TITLE:
 PDU, Basic
 ZERO U, 16A, 230V
 (20)C13 & (4)C19
 IEC309, 10 ft Cord
 GENERAL ARRANGEMENT

PROJECT: SUBMITTAL DRAWING **SHEET 1 OF 1**

| | |
|---------------------------------|---------------|
| DWG NO: AP7554 | REV: 0 |
| DRAWN: M.FIACCO/RANJITHA | 16-SEP-21 |
| ENGINEER: M.FIACCO | 16-SEP-21 |
| APPROVED: G.IVEY | 16-SEP-21 |
| THIRD ANGLE PROJECTION | |



VIEW A (ENLARGED)



VIEW B (ENLARGED)

