


# Product Environmental Profile

## Metered Rack Power Distribution Units (PDUs)


Metered, rack mounted PDUs that monitor their outlets and protects against power surges.



<b>Representative product</b>	Metered Rack Power Distribution Units (PDUs) - AP7800
<b>Description of the product</b>	A stand-alone, network-manageable power distribution device that monitors the total current drawn from its power outlets and protects from power surges.
<b>Description of the range</b>	Metered, rack mounted PDUs that monitor their outlets and protects against power surges. The environmental impacts of this referenced product are representative of the impacts of the other products of the range which are developed with a similar technology.
<b>Products covered</b>	AP78XX and AP88XX Series
<b>Functional unit</b>	Establish, support and interrupt for 10 years rated currents in normal conditions of the circuit characterized by the current 12/15A, for the operating voltage 100/120V, across 8 sockets.

## Constituent materials

**Reference product mass** 2910 g including the product, its packaging and additional elements and accessories



Plastics	9.7%
Metals	29.1%
Others	61.0%

## Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorized proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

As the products of the range are designed in accordance with the RoHS Directive (European Directive 2002/95/EC of 27 January 2003), they can be incorporated without any restriction in an assembly or an installation subject to this Directive.

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website <http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>

## Additional environmental information


The Metered Rack Power Distribution Units (PDUs) presents the following relevant environmental aspects

<b>Manufacturing</b>	Manufactured at a production site complying with the regulations
<b>Distribution</b>	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 1248.3 g, consisting of cardboard (93%), nylon (7%) and other plastics (1%) Product distribution optimized by setting up local distribution centers
<b>Installation</b>	The product does not require any special installation materials or operations. Installation is to be performed by qualified personnel.
<b>Use</b>	The product does not require special maintenance operations.
<b>End of life</b>	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains lithium metal coin battery (3g), electronic cards (406g), external electric cable (150g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End-of-Life Instruction document which is available on the Schneider-Electric Green Premium website <a href="http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page">http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page</a> Recyclability potential: <b>53%</b> Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

## Environmental impacts

<b>Reference lifetime</b>	10 years								
<b>Product category</b>	Combination of functions								
<b>Installation elements</b>	Transportation and disposal of packaging are accounted for during installation. No special installation components needed.								
<b>Use scenario</b>	Testing profile indicates an average loss of 0.952W and average annual consumption of 8.3kWh								
<b>Geographical representativeness</b>	The product can be used in all regions, but the majority of the product is deployed in Europe								
<b>Technological representativeness</b>	The means of material production, processing and transport modeled are representative of the technologies used in production.								
<b>Energy model used</b>	<table border="1"> <thead> <tr> <th>Manufacturing</th> <th>Installation</th> <th>Use</th> <th>End of life</th> </tr> </thead> <tbody> <tr> <td>Energy model used: India</td> <td>Electricity grid mix; AC; consumption mix, at consumer; &lt; 1kV; EU-27</td> <td>Electricity grid mix; AC; consumption mix, at consumer; &lt; 1kV; EU-27</td> <td>Electricity grid mix; AC; consumption mix, at consumer; &lt; 1kV; EU-27</td> </tr> </tbody> </table>	Manufacturing	Installation	Use	End of life	Energy model used: India	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27
Manufacturing	Installation	Use	End of life						
Energy model used: India	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27						

Compulsory indicators		Metered Rack Power Distribution Units (PDUs) - AP7800					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	6.43E-03	6.43E-03	0*	0*	3.55E-06	0*
Contribution to the soil and water acidification	kg SO <sub>2</sub> eq	2.38E-01	6.48E-02	1.71E-03	2.97E-04	1.70E-01	7.46E-04
Contribution to water eutrophication	kg PO <sup>3-</sup> eq	2.56E-02	1.45E-02	3.95E-04	9.92E-05	1.03E-02	3.29E-04
Contribution to global warming	kg CO <sub>2</sub> eq	7.09E+01	2.87E+01	3.75E-01	7.18E-02	4.09E+01	9.65E-01
Contribution to ozone layer depletion	kg CFC11 eq	5.55E-06	2.85E-06	7.61E-10	0*	2.66E-06	3.59E-08
Contribution to photochemical oxidation	kg C <sub>2</sub> H <sub>4</sub> eq	1.59E-02	6.37E-03	1.22E-04	2.23E-05	9.37E-03	6.58E-05
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m3	1.51E+02	2.64E+00	0*	0*	1.48E+02	0*
Total Primary Energy	MJ	1.37E+03	5.47E+02	5.31E+00	9.22E-01	8.16E+02	3.32E+00



Optional indicators		Metered Rack Power Distribution Units (PDUs) - AP7800					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	8.15E+02	3.42E+02	5.27E+00	9.46E-01	4.64E+02	3.10E+00
Contribution to air pollution	m³	4.90E+03	3.10E+03	1.60E+01	3.49E+00	1.76E+03	2.38E+01
Contribution to water pollution	m³	5.35E+03	3.54E+03	6.17E+01	1.06E+01	1.69E+03	4.54E+01
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	3.33E-01	3.33E-01	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	1.22E+02	1.81E+01	0*	0*	1.04E+02	0*
Total use of non-renewable primary energy resources	MJ	1.25E+03	5.29E+02	5.30E+00	9.19E-01	7.12E+02	3.31E+00
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	9.80E+01	0*	0*	0*	1.04E+02	0*
Use of renewable primary energy resources used as raw material	MJ	2.39E+01	2.39E+01	0*	0*	0*	0*
Use of non-renewable primary energy excluding non-renewable primary energy used as raw material	MJ	1.23E+03	5.10E+02	5.30E+00	9.19E-01	7.12E+02	3.31E+00
Use of non-renewable primary energy resources used as raw material	MJ	1.91E+01	1.91E+01	0*	0*	0*	0*
Use of non-renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	1.32E+01	1.02E+01	0*	0*	2.13E-02	3.07E+00
Non hazardous waste disposed	kg	1.94E+02	4.17E+01	0*	8.27E-02	1.52E+02	0*
Radioactive waste disposed	kg	1.10E-01	7.98E-03	0*	0*	1.02E-01	2.06E-05
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	2.31E+00	2.29E-01	0*	1.18E+00	0*	9.08E-01
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	2.48E-01	0*	0*	0*	0*	2.48E-01
Exported Energy	MJ	3.65E-03	3.43E-04	0*	3.31E-03	0*	0*

\* Represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.7.0.4, database version 2018-03 in compliance with ISO14044.

The use phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

According to this environmental analysis, proportionality rules may be used to evaluate the impacts of other products of this range.

The environmental indicators of other products in this family may be proportional extrapolated based on relationships between an amount of a key parameter of the product as compared to the amount of that key parameter within the reference product. Proportionality rules are based on the following key parameters: Manufacturing phase impacts - total mass of product. Distribution phase impacts - total mass of product (including packaging). Installation phase impacts - mass of packaging. Use phase impacts - life time energy use. End of Life impacts - the product mass (excluding packaging).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Registration number:	ENVPEP1712014_V2	Drafting rules	PCR-ed3-EN-2015 04 02
Verifier accreditation N°	VH-08	Supplemented by	PSR-0005-ed2-EN-2016 03 29
Date of issue	12/2018	Information and reference documents	<a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
		Validity period	5 years
Independent verification of the declaration and data, in compliance with ISO 14025: 2010			
Internal	X	External	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)			
PEP is compliant with XP C08-100-1 :2014			
The elements of the present PEP cannot be compared with elements from another program.			
Document in compliance with ISO 14025: 2010 « Environmental labels and declarations. Type III environmental declarations »			

Schneider Electric Industries SAS

Country Customer Care Center  
<http://www.schneider-electric.com/contact>

35, rue Joseph Monier  
 CS 30323  
 F- 92506 Rueil Malmaison Cedex  
 RCS Nanterre 954 503 439  
 Capital social 896 313 776 €

[www.schneider-electric.com](http://www.schneider-electric.com)  
 ENVPEP1712014\_V2