




DETAIL A  
IEC 309 16A,  
200-240VAC,  
L+N+PE PLUG  
ENLARGED VIEW




DETAIL B  
PEG TOOL LESS MOUNTING  
ENLARGED VIEW




DETAIL C  
UNIVERSAL MOUNTING BRACKET  
ENLARGED VIEW



DETAIL D  
ENLARGED SMART METER




ISOMETRIC VIEW



FRONT VIEW

LEFT SIDE VIEW



REAR VIEW

#### NOTES:

1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL ELECTRICAL CODES.
2. REFER TO PRODUCT DOCUMENTATION FOR ADDITIONAL DETAILS PRIOR TO INSTALLATION AND PREPARATION WORK.
3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS [INCHES].
4. NET WEIGHT OF UNIT IS 2.5kg [5.51 lb].
5. LENGTH OF THE CORD IS 3000mm [118 inches].
- △ 6. UNIVERSAL MOUNTING BRACKET IS AN ALTERNATIVE MOUNTING METHOD TO THE TOOL LESS MOUNT FOR 3RD PARTY ENCLOSURES. BRACKET IS PROVIDED WITH THE UNIT.
7. REFER TO WARNING LABEL ON REAR OF UNIT FOR SCREW MOUNTING.

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF SCHNEIDER ELECTRIC AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM SCHNEIDER ELECTRIC. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

**Schneider Electric**

TITLE: Easy PDU, Metered  
ZERO U, 16A, 230V  
INPUT: IEC309, L+N+PE  
OUTPUT: (18)IEC320 C13 & (3)IEC320 C19  
GENERAL ARRANGEMENT  
PROJECT: SUBMITTAL DRAWING SHEET 1 OF 2

DWG NO: EPDU1116M REV. 2  
DRAWN: JAYAPRAKASH 22-OCT-21  
ENGINEER: Troy LIU 22-OCT-21  
APPROVED: Tong XU 22-OCT-21  
FIRST ANGLE PROJECTION

