




DETAIL A  
IEC 309 16A,  
200-240VAC,  
L+N+PE PLUG  
ENLARGED VIEW




DETAIL B  
PEG TOOL LESS MOUNTING  
ENLARGED VIEW



DETAIL C  
UNIVERSAL MOUNTING BRACKET-LONG  
ENLARGED VIEW




DETAIL D  
UNIVERSAL MOUNTING BRACKET-SHORT  
ENLARGED VIEW



DETAIL E  
IDPU INSTRUMENT  
ENLARGED VIEW

#### NOTES:

1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL ELECTRICAL CODES.
2. REFER TO PRODUCT DOCUMENTATION FOR ADDITIONAL DETAILS PRIOR TO INSTALLATION AND PREPARATION WORK.
3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS [INCHES].
4. NET WEIGHT OF UNIT IS 7.3kg [16.09 lb].
5. LENGTH OF THE CORD IS 3000mm [118 Inches].
- △ 6. UNIVERSAL MOUNTING BRACKET IS AN ALTERNATIVE MOUNTING METHOD TO THE TOOL LESS MOUNT FOR 3RD PARTY ENCLOSURES. BRACKET IS PROVIDED WITH THE UNIT.
7. REFER TO WARNING LABEL ON REAR OF UNIT FOR SCREW MOUNTING.



ISOMETRIC VIEW

IEC309, 16A,  
200-240VAC,  
L+N+PE  
INPUT POWER CORD

M5 THREADED  
HOLE FOR  
EXTERNAL  
GROUNDING

POWER INDICATOR

REFER TO DETAIL-E

IEC320 C13  
(20 PLACES)

IEC320 C19  
(4 PLACES)

FRONT VIEW

LEFT SIDE VIEW

REAR VIEW

△ 6 UNIVERSAL  
MOUNTING BRACKET  
REFER TO DETAIL-C

PEG TOOL LESS  
MOUNTING  
(2 PLACES)  
REFER TO DETAIL-B

REFER TO  
DETAIL-A

△ 6 UNIVERSAL  
MOUNTING BRACKET  
REFER TO DETAIL-D


THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF SCHNEIDER ELECTRIC AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM SCHNEIDER ELECTRIC. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

**Schneider**  
**Electric**

TITLE: Easy PDU, Switched  
ZERO U, 16A, 230V  
INPUT: IEC309, L+N+PE  
OUTPUT: (20) IEC320 C13 & (4) IEC320 C19  
GENERAL ARRANGEMENT

PROJECT: SUBMITTAL DRAWING SHEET 1 OF 2

DWG NO:	EPDU1116S	REV:	1
DRAWN:	JAYAPRAKASH	22-OCT-21	FIRST
ENGINEER:	Troy LIU	22-OCT-21	ANGLE
APPROVED:	Tong XU	22-OCT-21	PROJECTION



#### NOTES:

1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL ELECTRICAL CODES.
2. REFER TO PRODUCT DOCUMENTATION FOR ADDITIONAL DETAILS PRIOR TO INSTALLATION AND PREPARATION WORK.
3. THIS DRAWING DEPICTS THE POWER SYSTEM CONNECTIONS AND IS NOT REPRESENTATIVE OF THE PHYSICAL LAYOUT. PLEASE REFER TO MECHANICAL DRAWINGS FOR PHYSICAL LAYOUT.

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF SCHNEIDER ELECTRIC AND SHALL NOT BE COPIED, REPRODUCED OR USED IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM SCHNEIDER ELECTRIC. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

**Schneider**  
**Electric**

TITLE: Easy PDU, Switched  
ZERO U, 16A, 230V  
INPUT: IEC309, L+N+PE  
OUTPUT: (20) IEC320 C13 & (4) IEC320 C19  
SCHEMATIC DIAGRAM

PROJECT: SUBMITTAL DRAWING SHEET 2 OF 2

DWG NO:	EPDU1116S	REV:	0
DRAWN:	JAYAPRAKASH	27-MAR-20	FIRST
ENGINEER:	Troy LIU	31-MAR-20	ANGLE
APPROVED:	Tong XU	31-MAR-20	PROJECTION