


LED spotlight

LED spotlight for defined accent lighting. Radiation angle 24° for retail applications and exhibitions. Total luminous flux: 3200 lm, Luminaire input power: 34 W. Luminaire efficacy: 95 lm/W. Lifetime: 50.000 h@ L70. Colour rendering Ra >90, colour temperature 4000 K, Chromaticity tolerance (initial MacAdam): 3. 3-phase universal track adapter. Spotlight rotatable through 350° and tiltable through 90°. Housing with integrated converter made of die-cast aluminium, colour white (RAL 9016). Dimensions: 146 x 79 x 179 mm, weight: 0.7 kg.




TE_LUCA_F_L_PERSP.jpg



TE_LUCA_M_L.wmf

Light Distribution

STD - standard



TE_LUCA_L_24°_940.ltd

- Light Source: LED
- Luminaire luminous flux*: 3219 lm
- Luminaire efficacy*: 95 lm/W
- Colour Rendering Index min.: 90
- Correlated colour temperature*: 4000 Kelvin
- Chromaticity tolerance (initial MacAdam): 3
- Rated median useful life*:
L70 50000 h at 25 °C
- Ballast: 1x LED_Con
- Luminaire input power*: 34 W Power factor = 0.97
- Dimming: Fixed output
- Maintenance category CIE 97: D - Enclosed IP2X
- Total harmonic distortion (THD): 18.00 %

This product contains a light source of energy efficiency class E.

All values marked with an * are rated values. Connected electrical load and luminous flux are subject to an initial tolerance of +/- 10%, the most similar colour temperature is subject to an initial tolerance of +/- 150K. Unless stated otherwise, the values apply to an ambient temperature of 25°C.